



## Class rules

**Drivetrain:** Front Wheel drive vehicle only.

**Body:** Any year vehicle allowed. Tubular body prohibited. One-piece front ends prohibited. Light weight 3 pieces' front end accepted. Other light weight components are limited to hood, fenders, sunroofs, roof, doors and hatches.

**Front overhang:** Maximum 45" from center of wheel bearing

**Chassis:** Must retain stock look with complete floor and firewall.

**Suspension:** Car must use stock front/rear suspension mount points. Aftermarket suspension, control arms and sub-frame are permitted. Wheelie bars are prohibited.

**Lights:** Headlights and brake lights are required (one headlight may be removed for induction)

**Interior:** Dash required. Aftermarket seat permitted. Passenger seat may be removed

**Doors:** Front doors must be functional and open with OEM handle from inside and outside. Lightweight doors like Jase and Seibon permitted, must retain OEM look.

**Windows:** The front windshield must be OEM glass. Side and back glass may be replaced with lexan or polycarbonate material. Side windows are not required to go up and down.

**Exhaust:** Not required. Exhaust may exit anywhere.

**Engine:** 4 & 6 cylinders allowed. 4 cylinders are limited to a 2.7L displacement maximum. 6 cylinders are limited to a 3.7 displacement maximum.

**Transmission:** Manual transmissions only. All automatic and sequential transmission prohibited.

**Shifter:** Shifter must be H-pattern. Strain gauges are permitted. Air shifters are prohibited.

**Fuel:** VP-M1, VP-M5 VP-C10, VP-C12, VP-C14, VP-C14+, VP-C16, FTW & Ethanol based fuel permitted. Aftermarket fuel cell accepted and can be mounted in the front or at the OEM location. Nitromethane use permitted for all engines except for Honda K-Series.

**Power Adders:** Prohibited

**Tires:** Racing slicks tires only. Maximum size slick bias ply tire is 25" x 10"

**Weight limit:** Weight is monitored after each qualification and elimination pass. Failure to pass on the scale after a run will invalidate the run.

Make	Series	Car & Driver minimum Weight
Honda	B series	1700 lbs.
Honda	H or H2B series	1800 lbs
Honda	K or F2K series	2050 lbs. (99mm stroke can go 1900 lbs.)
Honda	J Series	2100 lbs.
VW	2.0L	1800 lbs.
VW	VR6	2100 lbs.
Nissan	QR or SR20	1800 lbs.

## Security Rules

**Helmet:** Required

**Engine containment device:** Catch pan or engine diaper to catch oil or debris mandatory. Engine and transmission must be covered.

**Protective clothing:** Jacket and gloves required

**Seat Belts:** 5 points seat belts required for all cars with 10 points roll cage. OEM seat belt mandatory for all other cars.

**Parachute:** Required for all cars running 150mph and higher (warning will be given for first timers, racer will have to comply for the next event race)

**Roll Cage:**

- 5 points roll cage minimum required for cars running 11.49 or lower

- 10 points roll cage required for cars running 9.99 or lower

**\*\*\* All racers must wear pants; no shorts will be tolerated! \*\***