



Class rules

Drivetrain: Front Wheel drive vehicle only.

Body: Any year vehicle allowed. Tubular body prohibited. One-piece front ends prohibited. Light weight 3 pieces' front end accepted. Other light weight components are limited to hood, fenders, sunroofs, roof, doors and hatches.

Front overhang: Maximum 45" from center of wheel bearing

Chassis: Must retain stock look with complete floor and firewall.

Suspension: Car must use stock front/rear suspension mount points. Aftermarket suspension, control arms and sub-frame are permitted. Wheelie bars are prohibited.

Lights: Headlights and brake lights are required (one headlight may be removed for induction)

Interior: Dash required. Aftermarket seat permitted. Passenger seat may be removed

Doors: Front doors must be functional and open with OEM handle from inside and outside. Lightweight doors like Jase and Seibon permitted, must retain OEM look.

Windows: The front windshield must be OEM glass. Side and back glass may be replaced with lexan or polycarbonate material. Side windows are not required to go up and down.

Exhaust: Not required. Exhaust may exit anywhere.

Engine: 4 & 6 cylinders allowed.

Transmission: Manual transmissions only. All automatic and sequential transmission prohibited.

Shifter: Shifter must be H-pattern. Strain gauges are permitted. Air shifters are prohibited.

Fuel: Methyl alcohol prohibited (VP-M1, VP-M5), all other gas permitted. Aftermarket fuel cell accepted and can be mounted in the front or at the OEM location.

Ground clearance: Must be at least 3" between front bumper and the firewall. (a tester will be available at the scale during the event)

Nitrous: Permitted, must add 100lbs to car weight limit

Tires: Racing slicks only. Maximum size slick bias ply tire is 25" x 9.5"

Weight limit: Weight is monitored after each qualification and elimination pass. Failure to pass on the scale, run will not be valid.

Engine	Turbo measurements	Car & Driver minimum Weight
4 & 6 cylinder	62mm or less	2100 lbs.
4 & 6 cylinder	67.9mm inducer / 94.8mm Exducer	2200 lbs.
4 & 6 cylinder	67.9mm inducer / 102.9mm Exducer	2300 lbs.
4 & 6 cylinder	72mm Inducer / 102.9mm Exducer 72mm Inducer / 106.9mm Exducer	2400 lbs.

Security Rules

Helmet: Required

Engine containment device: Catch pan or engine diaper to catch oil or debris mandatory. Engine and transmission must be covered.

Protective clothing: Jacket and gloves required

Seat Belts: 5 points seat belts required for all cars with 10 points roll cage. OEM seat belt mandatory for all other cars.

Parachute: Required for all cars running 150mph and faster (warning will be given for first timers, racer will have to comply for the next event race)

Roll Cage:

- 5 points roll cage minimum required for cars running 11.49 or lower

- 10 points roll cage required for cars running 9.99 or lower

***** All racers must wear pants; no shorts will be tolerated! *****